

Precision Battery Hydrometers

CAT.NO.	DESCRIPTION	SUB.DIV.	ACCURACY	TEMP.
QBAT118126	Battery Hydrometer 1180-1260 SG	0.005SG	0.005SG	25°C.
QBAT118132D	Battery Hydrometer 1180-1320 Density	5kg/m3	5kg/m3	30°C.
QBAT885	Battery Hydrometer 0.800-0.850 SG Float	0.002SG	0.002SG	15.6°C.
QBAT885C	Battery Hydrometer 0.800-0.850 SG Comp.			

Iso Propyl Alcoholometers

CAT.NO.	DESCRIPTION	SUB.DIV.	ACCURACY	TEMP.	APPROX.LNG
IP020	IsoPropyl Alcoholometer 0-20	1%/Vol.	1%/Vol.	20°C.	185mm
IP02010	IsoPropyl Alcoholometer 0-20 @10°C	1%/Vol.	1%/Vol.	10°C.	185mm

For accurate determination of IPA used in the printing industry.

Salinometers

CAT.NO.	DESCRIPTION	SUB.DIV.	ACCURACY	TEMP.	APPROX.LNG
SAL0100	Salinometer 0-100	1%	2%	15.6°C.	260mm

Note.

These hydrometers read % saturated salt, that is, a reading of 100 percent indicates that no more salt will dissolve in the solution.

Soil Hydrometers to A.S.T.M. 152H & 151H

CAT.NO.	DESCRIPTION	SUB.DIV.	ACCURACY	TEMP.	APPROX.LNG
TS1038	Soil Hydrometer 0.995-1.038 SG	0.001SG	0.001SG	20°C.	
TS560	Soil Hydrometer -5/60 g/l	1g/lt	1g/lt	20°C.	

PLEASE NOTE: All details and descriptions in this catalogue are subject to change without notice. Please contact Carlton Glass for current details of all products.